


**REMARKS**

The foregoing amendments to claims 3-13 are to remove multiple dependencies and to remove the word "preferably" for greater clarity. Favorable consideration of the application is respectfully requested.

Respectfully submitted,



Robert B. Smith

PTO Registration No. 28,538

Attorney for applicant(s)

(212) 735-3020

106080-26252660

VERSION WITH MARKINGS TO SHOW CHANGES MADE

3. (Amended) A support according to claim 1 [or 2], characterized in that said support (15; 25; 35) is made of elastic materials.

4. (Amended) A support according to [any one of claims 1-3] claim 1, characterized in that said one or more electrically connecting supports (151; 251; 252; 351) are made of elastomeric materials.

5. (Amended) A support according to [any one of claims 2-4] claim 2, characterized in that said electrically conducting material (1511; 2511; 3511) consists of silicone rubber with a concentration of carbon black sufficient for electrical conduction.

6. (Amended) A support according to [any one of claims 1-5] claim 1, characterized in that said cartridge (40) has an axial direction of symmetry (41), and said information carrying areas (401, 402; 403, 404; 405 406; 410, 411, 412, 413, 414) are located [preferably in] at one axial end of the cartridge.

7. (Amended) A support according to [any one of claims 1-5] claim 1, characterized in that said cartridge (40) has an axial direction of symmetry (41), and said information carrying areas (415) are located [preferably] in an axial direction of the cartridge covering only a limited angular sector (421).

8. (Amended) A support according to [any one of claims 1-7] claim 1, characterized in that said support (15; 35) comprises one electrically connecting

support (151; 351) [preferably] stretching in an axial direction of the cartridge (10; 30).

9. (Amended) A support according to [any one of claims 1-7] claim 1, characterized in that said support (25; 70) comprises two or more electrically connecting supports (251, 252; 701, 702, 703) each stretching [preferably] in an axial direction (21; 72) of the cartridge (20; 71) and being located side by side along the radial periphery of the cartridge.

10. (Amended) A support according to [any one of claims 1-9] claim 1, characterized in that the surface of the support (15; 25; 35) facing towards the cartridge (10; 20; 30), including the one or more electrically connecting supports (151; 251, 252; 351), in an axial cross section correspond to the surface of the cartridge.

11. (Amended) A support according to [any one of claims 1-9] claim 1, characterized in that the surface of the support (70) facing towards the cartridge (71), including the one or more electrically connecting supports (701, 702, 703), in an axial cross section essentially correspond to the surface of the cartridge, when said cartridge is positioned in said support.

12. (Amended) A support according to [any one of claims 1-11] claim 1, characterized in that said cartridge (10) has an axial direction of symmetry (11), and said contact area (163) consists of groups of identical and regularly spaced electrically conducting pads (62) of width  $W_{cp}$  (620) in the direction of adjacent

pads, adjacent pads being separated by an electrically insulating area of width Diacp (621), and the following relations between said distances are fulfilled:

$\text{Diacp} > 2 * \text{Tcl}$ , and

$\text{Wcp} > \text{Til} + \text{Tcl}$ .

13. (Amended) A support according to [any one of claims 1-12] claim 1, characterized in that said cartridge (20) has an axial direction of symmetry (21), and said cartridge is provided with a multitude of rectangular, essentially parallel, identically sized information carrying areas (810, 820, 830, 840, 850, 860) of height Hica (87) in the direction of a circumference (80) of said axis of symmetry (21), said information carrying areas being spaced with equal mutual distance Dica (88) along the periphery of the cartridge in the direction of a circumference (80) of said axis of symmetry (21), and said supporting means (25) comprise two rectangular, essentially parallel, identical electrically connecting supports (251, 252; 81, 82) of height Hctm (85) in the direction perpendicular to the axis of symmetry of the cartridge, separated by an electrically insulating volume (255) of width Dctm (86) between the two electrically connecting supports, and the following relations between said distances are fulfilled:

$\text{Hica} < \text{Dctm} < 2 * \text{Hica} + \text{Dica}$ , and

$\text{Hctm} < \text{Dica} < 2 * \text{Hctm} + \text{Dctm}$ .

09925792-080901